



DEVILLE
RECTIFICATION

Buderus | Edelstahl



5083

*Aluminium alloy
(Al Mg 4.5 Mn) (AG 4.5)
TEMPER Rolled H111*



Chemical analysis (weight %) Min. Max.

	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	Other	Al
Min.				0.40	4.00	0.05				
Max.	0.40	0.40	0.10	1.00	4.90	0.25	0.25	0.15	0.15	remains

Performance properties and aptitudes :

Very good thermal conductivity. Excellent corrosion resistant in normal and marine atmospheres. Excellent weldability (TIG/MIG and resistance welding). Good machinability. Excellent technical anodisation; average decorative anodisation.

Tensile strength	250 MPA
Limit of elasticity Rp 0.2	130 MPA
Elongation %	13
Hardness HB	75
Specific gravity	2.78
Thermal conductivity W / m.k	110 - 140
Electric conductivity m/Ohm.mm ²	16 - 19
Thermal stress coefficient 10-6/K	23.3
Modulus of elasticity MPA	70,000

Non-contractual document 10 October 2011 edition

DEVILLE RECTIFICATION

Z.I Desforanges
Boite postale 3
F-43330 Pont-Salomon



Tél : + 33 (0)4 71 66 29 71

Fax : + 33 (0)4 71 66 29 72

Com@deville-rectif.com

www.deville-rectif.com